

- Drying surface capture-type ultrafiltration membrane
- comprises swelling membrane having outer skin by
wetting with hydrophilic organic solvent and drying,
preventing fibres adhering.

L20 ANSWER 99 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 1992-426400 [52] WPINDEX

DNC C1992-189061

DC A26 A35 A88 J01

PA (NIOD) NOK CORP

CYC 1

PI JP 04317726 A 19921109 (199252)* 2p

ADT JP 04317726 A JP 1991-110927 19910416

PRAI JP 1991-110927 19910416

AN 1992-426400 [52] WPINDEX

AB JP 04317726 A UPAB: 19931006

To **clean** the ultrafiltration **membrane** having an outer
surface skin layer it is swelled by wetting it with hydrophilic organic
solvent and is then dried.

USE/ADVANTAGE - Used for drying surface catching type ultrafiltration
membrane esp. for drying hollow fibre membrane directly after gelation and
rinsing processes. The method prevents fibres from sticking to each other
and gives hollow fibre membranes without deteriorating the skin layers.

In an example hollow fibre membranes that have skin layer on their
outside surface, were wet spun from polysulphone. They were immersed
into 99.5% ethanol were made to dry in warm (50 deg.C) **air**
flow. Sticking between fibres was not observed. Permeability of
water through the membrane and the fractionation characteristics were
homogeneous.

0/0